

KERNEBOREMASKINE
PROFIBASIC


MABasic 200

Optagen effekt (Watt)	900
Volt	230
Omdrejningstal (o/min)	450
Vandring (mm.)	160
Magnet størrelse i mm. (B x L x H)	84 x 168 x 48
Kernebør kort 30 mm. lang 55 mm.	12-32 12-32
Spiralbor (max. Ø mm.)	op til 13
Max. boreddybde i stål (mm.)	30/55
Kerneborepatron	19 mm Weldon (3/4")
Indvendig smøring	✓
Vægt (kg)	12,00
Art. nr.	MABasic 200
DKK	6.700,00
Lager	✓

KERNEBOREMASKINE
PROFIBASIC


MABasic 400

Optagen effekt (Watt)	1.050
Volt	230
Omdrejningstal (o/min)	430 760
Vandring (mm.)	160
Magnet størrelse i mm. (B x L x H)	84 x 160 x 41,5
Kernebør kort 30 mm. lang 55 mm.	12-35 12-35
Spiralbor (max. Ø mm.)	op til 16
Max. boreddybde i stål (mm.)	35
Kerneborepatron	19 mm Weldon (3/4")
Indvendig smøring	✓
Vægt (kg)	12,0
Art. nr.	MABasic 400
DKK	11.200,00
Lager	✓



MABasic 450

Optagen effekt (Watt)	1.150
Volt	230
Omdrejningstal (o/min)	250 450
Vandring (mm.)	160
Magnet størrelse i mm. (B x L x H)	84 x 168 x 41,5
Kernebor kort 30 mm. lang 55 mm.	12-40 12-40
Spiralbor (max. Ø mm.)	op til 18
Max. boreddybde i stål (mm.)	30/55
Kerneborepatron	MK2, 19 mm Weldon (3/4")
Indvendig smøring	✓
Vægt (kg)	13,0
Art. nr.	MABasic 450
DKK	11.900,00
Lager	✓



MABasic 850

Optagen effekt (Watt)	1.800
Volt	230
Omdrejningstal (o/min)	Gear 1: 110 Gear 2: 175 Gear 3: 425 Gear 4: 385
Vandring (mm.)	255
Magnet størrelse i mm. (B x L x H)	110 x 220 x 54
Kernebor kort 30 mm. lang 55 mm. lang 75 mm ekstra lang 110 mm.	12 - 75 2 - 75 18 - 60 20 - 60
Spiralbor (max. Ø mm.)	31,75
Max. boreddybde i stål (mm.)	110
Kerneborepatron	MK 3, 19 mm Weldon (3/4") MK 3, 32 mm Weldon (1 1/4")
Spindelkonus	MK 3
Indvendig smøring	✓
Vægt (kg)	24,0
Art. nr.	MABasic 850
DKK	14.950,00
Lager	✓